

141



विहार सरकार

Government of Bihar
Department of Social Welfare



सुरक्षित बचपन - विकसित समाज

STATE CHILD PROTECTION SOCIETY, BIHAR

2nd Floor, Apnagar (Behind Lalit Bhawan), Bailey Road, Patna-23, Bihar. ✉-scpsbihar@gmail.com ☎-06122545033

Bid No.: 01/2016

**CENTRALIZED BID NOTICE FOR
SUPPLY AND INSTALLATION OF VARIOUS ITEMS FOR OFFICE USE.**

Sealed Bid is hereby invited from interested bidders for supply and installation of items as per Annexure - II under two-bid system for various districts of Bihar. Further details containing nature, requirements and scope of work is available in Bid Documents, which can be downloaded from the website of SOCIAL WELFARE DEPARTMENT (www.socialwelfare.bih.nic.in).

The timeline for bid process is given below;

Sl. No.	Items	Date & Time
1	Information about Notice Inviting Bid and availability of Bid Document on website www.socialwelfare.bih.nic.in or in office of STATE CHILD PROTECTION SOCIETY Bihar	21/10/2016, 11:00 Am.
2	Last date and time for receipt of Bids	11/11/2016, 02:00 pm
3	Opening of Bid	11/11/2016, 03:00 pm

Sealed Bids would be submitted through Speed Post / registered Post / Courier/by hand on any working day on or before due date and time at STATE CHILD PROTECTION SOCIETY, 2nd floor, Apna Ghar, Behind Lalit Bhawan, Bailey Road, Patna-800023.

Handwritten signature

**Project Director,
State Child Protection Society,
Directorate of Social Welfare, Bihar**

2/10



बिहार सरकार

Government of Bihar
Department of Social Welfare



STATE CHILD PROTECTION SOCIETY, BIHAR

2nd Floor, Apnagar (Behind Lalit Bhawan), Bailey Road, Patna-23, Bihar. ✉ scpsbihar@gmail.com ☎ -06122545033

BID DOCUMENT

FOR SUPPLY AND INSTALLATION OF ITEMS FOR VARIOUS DISTRICTS OF BIHAR

Last Date for Submission: 11/11/2016

Date of Opening: 11/11/2016

Bid Notice

Sealed bids are invited for supply and installation of items as per Schedule I with specification as mentioned in *Annexure – III* for the STATE CHILD PROTECTION. The detailed terms and conditions can be downloaded from the website of SOCIAL WELFARE DEPARTMENT www.socialwelfare.bih.nic.in

Bids shall be submitted through Two Envelopes System namely TECHNICAL BID & FINANCIAL BID

Technical Bid shall consist of the Eligibility criteria consisting the following :

- Bid document can be purchased from **STATE CHILD PROTECTION SOCIETY** at **Patna** up to one day prior to the last date of submission of the bid by paying Rs 1000.00 (One thousand only) in the form of demand draft favoring PARIYOJANA NIDESHAK, RAJYA BAL SANRAKSHAN SAMITI and payable at Patna. Those who are downloading bid document from website have to deposit a Demand Draft of Rs. 1,000.00 (One thousand only) along with bid document in technical bid envelop.
- Tenders must be in one large envelope marked as “Supply and Installation of various items at STATE CHILD PROTECTION SOCIETY” with enclosing two separate envelope marked as:
 - ◆ Technical Bid dully signed, sealed and filed Annex-I, II, IV.
 - ◆ Financial Bid dully signed, sealed and filed - Annexure-III.

• **Earnest Money Deposit:-**

EMD	For Schedule – I	Rs. 2,20,000/-
	For Schedule – II	Rs. 1,45,000/-
	For Schedule – III	Rs. 1,10,000/-
TOTAL		Rs. 4,75,000/-

Demand Draft favoring PARIYOJANA NIDESHAK, RAJYA BAL SANRAKSHAN SAMITI and payable at Patna has to be submitted.

- Bidder/s may quote for any or all schedules listed under Annexure - II.
- Prices quoted for each schedule shall correspond 100 percent of the quantities specified in the respective schedule. If the bidder did not quote all item as mentioned in the respective schedule then in that case the bid shall be summarily rejected.

Signature

- Past performance experience certificate of bidding for any Government/semi Govt./reputed corporate bodies. The bidder must submit a copy of executed purchase orders during last three financial years. In this regard *Annexure – IV* must be filled in.
- Proof of sound financial capability of the bidder. The Bidder should have achieved minimum **AVERAGE** sales Turnover of Rs. 50 Lacs during last three consecutive financial years and should furnish Profit & Loss statement, Balance sheet for Last 3 financial year's i.e. 2013-2014, 2014-2015 and 2015-2016, in support of its financial standing and capability to perform the contract on time.
- Banker certificate showing the financial solvency of firm to execute this work.
- Registration certificate of bidder under suitable act e.g. Shop and Establish Act/ Company Act, etc.
- Warranty of each item must be specifically quoted, including the standard warranty and extended warranty, if any given by the bidder.
- The bidder should have been registered with concerned sales tax authorities. Copy of such certificate of sales tax return shall be enclosed as a proof.
- Undertaking that the bidder is not black listed from any Govt. or semi Govt. Organization and an affidavit to this effect duly notarized must be submitted along with the bid. The affidavit must be dated after the bid publication date.
- Bids shall remain valid for 90 days after the deadline for submission of bids prescribed by the STATE CHILD PROTECTION SOCIETY, Bihar. A bid valid for a shorter period shall be rejected by the STATE CHILD PROTECTION SOCIETY, Bihar as non-responsive.
- The bid form should be filled legibly or typed. The bid form should be signed by the bidder himself. The forwarding letter should be signed along with PAN allotted by the Income Tax Department.
- It is required that the goods under the Invitation for Bids shall be delivered by the successful bidder within **14 days** from the date of award of work order. **Otherwise penalty @ 1% per week** on the residual bill would be levied for delay up to three weeks. After that the STATE CHILD PROTECTION SOCIETY would reconsider the work order granted to the bidder.
- Supply of inferior quality of goods means diversion from the specifications as mentioned in Annexure - II will attract necessary legal action apart from forfeiture of performance guarantee.
- Bidder submitting a bid would be presumed to have considered and accepted all the terms and conditions. No inquiry verbal or written shall be entertained in respect of acceptance/rejection of the bid.
- Any act on the part of the bidder to influence anybody in the Directorate is liable to rejection of his bid.
- The successful bidder shall provide such packing of goods as is required to prevent their damage or deterioration during transit to their final destination as indicated in the contract. The packing shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit and open storage.
- Bid must be unconditional.

α

- The agency shall not engage any sub-contractor or transfer the contract to any other person in any manner.
- EMD of unsuccessful bidders will be discharged at the earliest or latest before the 30th day after award of work to the successful bidder and signing of contract thereof.
- In case of dispute or difference the court at Patna shall only have the jurisdiction over the same.

Submission Requirements

Interested Bidders wishing to undertake the above may submit in Sealed large envelopes marked

- (1) Bid for various goods Marked as - "Technical Bid", Annexure- I, II and IV
- (2) Bid for various goods Marked as - "Financial Bid", Annexure- III

Both the above sealed envelopes will then be put & sealed in an outer envelope addressed to Vice-Chairperson, STATE CHILD PROTECTION SOCIETY mentioning the bid number, due date & time for opening. Envelope marked 'FINANCIAL' – shall contain financial bid, i.e. rates only. The Specification of goods to be supplied and installed is written in Annexure- II.

Bid Price & General Conditions

1. Technical Bid will be opened first and the qualifying eligibility and other documents submitted by the Bidder will be evaluated at first stage. The financial bid of those bidders will only be opened, whose other documents will be found satisfactory and according to instructions and specification.
2. Bidders will have to quote single rate strictly as per the technical specification.
3. Successful bidder shall have to submit 5 % as performance security of the ordered value. The performance security can be either in the form of Bank draft or Bank Guarantee.
4. The STATE CHILD PROTECTION SOCIETY will award the contract to the bidder whose Bid has been determined to be substantially responsive and who has offered the lowest evaluated Bid price on bid for each particular item. Notwithstanding the above, the STATE CHILD PROTECTION SOCIETY reserves the right to accept or reject any Bid and to cancel the bidding process and reject any/all Bids at any time prior to the award of the contract.
5. Payment shall be made by the STATE CHILD PROTECTION SOCIETY when bills with delivery challan duly signed by the competent authority are submitted on delivery of the goods in satisfactory condition. **Payment shall be made after deduction of VAT and other statutory deductions.**
6. No price preference will be given to any agency irrespective of any registration.
7. The order may be placed in phases, or partially over a period of time at the full discretion of the purchase.
8. **Force Majeure**
 - The supplier shall not be liable for forfeiture of its performance security, liquated damage or termination for default, if and to the extent that, it's delay in performance or other failure to perform its obligation under the contract is positively the result of an event of force majeure.


- For the purpose of this clause, "force majeure" means an event beyond the control of the supplier and not involving the supplier's fault or negligence and not foreseeable. Such events may include, war or revolutions, fire, flood, epidemics, quarantine restrictions and freight embargo.
- If a force majeure situation arises, the supplier shall promptly notify the Society in writing of such conditions and the cause thereof. Unless otherwise directed by the Society in writing, the supplier shall continue to perform its obligations under the contract as far as is reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the Force majeure event.

Submission of Bid:

The bid must reach the office of the STATE CHILD PROTECTION SOCIETY by 02:00 pm on or before 11th November, 2016 latest through Registered post/ Courier / Speed Post/ by Hand. Bids received after this would not be entertained on any ground. The bid will be opened on 11th November, 2016 at 03:00 pm in the presence of the bidders or their authorized representatives.

In case the Agency / firm decline to take up the task after being awarded the Contract, it would be debarred for a period of three years from the date of award.

The decision of the STATE CHILD PROTECTION SOCIETY shall be final and no inquiries or application for review shall be entertained. The STATE CHILD PROTECTION SOCIETY reserves the right to cancel or reject any/all bid/s without assigning any reason.



**Project Director,
State Child Protection Society,
Directorate of Social Welfare, Bihar**

ANNEXURE-1 - TECHNICAL BID

BID FORM FOR SUPPLY AND INSTALLATION OF VARIOUS GOODS FOR PRE QUALIFICATION OF BID

1. Names & address of firm /Agency and contact number: _____

2. Registration No. of the firm/Agency: _____

3. VAT Registration Details:

4. Copy of PAN:

5. Name, designation, address & contact no. of authorized person of Firm/Agency to deal

with: _____

6. Please specify as to whether bidder is a sole Proprietor/Partnership Firm Name, Address and contact no. of Director / Partner should be specified:

a) _____ b) _____

c) _____ d) _____

7. Details of Earnest Money Deposit:

a) Amount. _____ (in words) _____

b) Bank draft No.: _____

c) Date of issue of BD: _____

d) Name of the issuing bank: _____

8. Details of experience with regard to printing with full details of the agency(s) to who such work order awarded along with copies of work satisfactory reports should be attached. In case number of such agencies is more, then a separate sheet may be used for indicating experience for printing:

9. Any other information:

10. Declaration of bidder to be registered with Bihar Sales Tax authority before the award of work order, if the bidder is outside the state of Bihar.

11. Declaration by the bidder – This is to certify that I/We before signing this bid have read and fully understood all the terms and conditions contained herein and undertake myself /ourselves to abide by them.

(Signature/s of Bidder/s)

Name: _____

Designation: _____

Address: _____

Phone No. : _____ (O)

Phone No. : _____ (R)

134

ANNEXURE-II

Detailed Specification with quantity of goods to be procured

Schedule – I

Sl. No.	Name of the Item	Specification	Quantity	Place of Delivery	
1.	LED TV – 42”	USB Port-1, HDMI port-2, Model year 2015 or above, Screen Size – 42”, Screen type- LED, resolution- full HD, feature- Full HD TV.	45	Patna, Araria, Begusarai, Kaimur, Munger, Bhagalpur, Bhojpur, Darbhanga, East Champaran, Gaya, Gopalganj, Jehanabad, Katihar, Saharsa, Kishanganj, Madhepura, Madubani, Muzaffarpur, Nawada, Purnea, Samastipur, Saran, Sitamarhi, Siwan, Vaishali, Nalanda and West Champaran. (Total-27 Districts of Bihar)	
2.	HD Dish Connection	Type- HD, Recording- YES, Pack type- HD	45		
3.	Single door Refrigerator with Stabilizer	Gross storage capacity- 245ltr, 220V, 50 Hz, Frost free, Insulation- Puff/Maxi 2/ Polyurethane, CFC free, Power saver compressor, Metallic colour.	45		
4.	Washing machine	Fully Automatic Front Load, Washing Capacity-7kg, Washing method- Tumble wash, Spin speed- 800 rpm or above	60		
5.	Geysers	Capacity-50 L, 375mmX385mmX840mm (HXWXB) External Temperature Indicator, 230V, 50Hz, IPX4 Technology to protect electrical parts from water splash.	60		
6.	Air Cooler	Water tank Capacity- 35 or above, Blower control- 3 or above, Body- ABS Plastic with water level indicator.	240		
7.	Wall mounted RO Water Purifier	No of Purification stages:	4		60
		Purification capacity	15 Litre per hour		
		Installation:	Wall Mounted		
		Membrane Type:	Thin Film Composite RO		
		Dimension (WxDxH):	270x505x380 mm		
		Weight:	8.6 kg		
		Operating Voltage:	300V 24V		
		Warranty:	1 Year(s)		
		Application:	Suitable for purification of Brackish, Tap Water		
		Purification Technology:	RO+UV+UF+TDS		
		Storage Capacity:	Minimum 9 Litre(s)		
Filter Cartridge:	Carbon Block Filter, Sediment, UF & Post Carbon				
Operations	Fully Automatic with auto cut-off				
8.	Exhaust Fan	Sweep Size-300mm, No of blade-3, Finish-Metallic, Air delivery-900 CMH or above, speed-1350 RPM or above, Noise level-45-50 db or less,	60		
9.	Search Light (Torch)	Any material, LED details- 4.0 V, 700mA, 140 Lumen, Package- Carton, LED- 3 W, battery operated cum rechargeable.	120		
10.	Room Heater	Type: Room Heater, Heat setting: 400W/800W/1200W, Power Consumption: 1200W, Heating element: Halogen tubes, No. of Heat setting: 3/4, Power Source: Electric, Feature: Silent Running	120	In above mentioned dists. excluding Kishanganj (Total-26 dists.)	

11.	Inverter with Battery	<p>Inverter:</p> <table border="1"> <tr> <td>Rating</td> <td>1400 VA/ 5 KVA.</td> </tr> <tr> <td rowspan="3">Input</td> <td>Voltage range</td> <td>110V-280V AC</td> </tr> <tr> <td>Frequency Range</td> <td>50Hz +/- 5Hz</td> </tr> <tr> <td>AVR</td> <td>Four steps AVR 220v±10%</td> </tr> <tr> <td rowspan="3">Output</td> <td>Inversion voltage</td> <td>220V±3%</td> </tr> <tr> <td>Inversion frequency</td> <td>50Hz±2%</td> </tr> <tr> <td>O/P waveform</td> <td>Sine wave</td> </tr> <tr> <td>DC voltage</td> <td>24V</td> </tr> <tr> <td>THD</td> <td>≤3%</td> </tr> <tr> <td>Transfer time</td> <td>≤4ms Automatic transfer</td> </tr> <tr> <td>Recharge current</td> <td>10A-15A</td> </tr> <tr> <td>Transfer efficiency</td> <td>85%</td> </tr> <tr> <td>Protections</td> <td>Protection against short-circuit, overload</td> </tr> <tr> <td>Communication ports</td> <td>RS 232</td> </tr> <tr> <td>Unit size (mm)</td> <td>372*122*195</td> </tr> <tr> <td>Net weight (Kg)</td> <td>13.5</td> </tr> <tr> <td>Gross weight (Kg)</td> <td>14.9</td> </tr> <tr> <td>Shipping size (mm)</td> <td>490*236*290</td> </tr> </table> <p>Battery:</p> <table border="1"> <tr> <td>Battery Type</td> <td>Tall Tubular</td> </tr> <tr> <td>Support</td> <td>Power Outage</td> </tr> <tr> <td>Electrolytes Volume</td> <td>Minimum 38 Litre</td> </tr> <tr> <td>Rating</td> <td>200 Ah and above</td> </tr> <tr> <td>Voltage</td> <td>12 Volt</td> </tr> <tr> <td>Weight</td> <td>Not more than 58.5 kg</td> </tr> <tr> <td>Dimension</td> <td>Not less than 54x23x44 cm</td> </tr> <tr> <td>Warranty</td> <td>Minimum 36 months</td> </tr> </table>	Rating	1400 VA/ 5 KVA.	Input	Voltage range	110V-280V AC	Frequency Range	50Hz +/- 5Hz	AVR	Four steps AVR 220v±10%	Output	Inversion voltage	220V±3%	Inversion frequency	50Hz±2%	O/P waveform	Sine wave	DC voltage	24V	THD	≤3%	Transfer time	≤4ms Automatic transfer	Recharge current	10A-15A	Transfer efficiency	85%	Protections	Protection against short-circuit, overload	Communication ports	RS 232	Unit size (mm)	372*122*195	Net weight (Kg)	13.5	Gross weight (Kg)	14.9	Shipping size (mm)	490*236*290	Battery Type	Tall Tubular	Support	Power Outage	Electrolytes Volume	Minimum 38 Litre	Rating	200 Ah and above	Voltage	12 Volt	Weight	Not more than 58.5 kg	Dimension	Not less than 54x23x44 cm	Warranty	Minimum 36 months	60	<p>Patna, Araria, Begusarai, Kaimur, Munger, Bhagalpur, Bhojpur, Darbhanga, East Champaran, Gaya, Gopalganj, Jehanabad, Katihar, Saharsa, Kishanganj, Madhepura, Madubani, Muzaffarpur, Nawada, Purnea, Samastipur, Saran, Sitamarhi, Siwan, Vaishali, Nalanda and West Champaran. (Total-27 Districts of Bihar)</p>
Rating	1400 VA/ 5 KVA.																																																									
Input	Voltage range	110V-280V AC																																																								
	Frequency Range	50Hz +/- 5Hz																																																								
	AVR	Four steps AVR 220v±10%																																																								
Output	Inversion voltage	220V±3%																																																								
	Inversion frequency	50Hz±2%																																																								
	O/P waveform	Sine wave																																																								
DC voltage	24V																																																									
THD	≤3%																																																									
Transfer time	≤4ms Automatic transfer																																																									
Recharge current	10A-15A																																																									
Transfer efficiency	85%																																																									
Protections	Protection against short-circuit, overload																																																									
Communication ports	RS 232																																																									
Unit size (mm)	372*122*195																																																									
Net weight (Kg)	13.5																																																									
Gross weight (Kg)	14.9																																																									
Shipping size (mm)	490*236*290																																																									
Battery Type	Tall Tubular																																																									
Support	Power Outage																																																									
Electrolytes Volume	Minimum 38 Litre																																																									
Rating	200 Ah and above																																																									
Voltage	12 Volt																																																									
Weight	Not more than 58.5 kg																																																									
Dimension	Not less than 54x23x44 cm																																																									
Warranty	Minimum 36 months																																																									
12.	Sewing Machine	<p>Bobbin System-Auto tripping, Button whole sewing-four step, Size-381mm X 205mm X 288mm, No of stich function- 13 or above</p>	75	<p>Patna, Purnea, Begusarai, Bhagalpur, E.Champaran, Saharsa, Saran, Kishanganj, Madhubani, Muzaffarpur & Gaya (Total-11)</p>																																																						
13.	Ceiling Fan	<p>Fan Size- 48", Sweep-1200 mm, RPM- 850 RPM, Blade-3, number of speed setting-5.</p>	5	Patna																																																						
14	Wall Fan	<p>3 Blade Cabin Fan, Size: 12 Inch, High speed motor, Gyroscopic movement, High Quality Material, Sweep: 300 MM, Power Input:58W, Speed: 1330 RPM, Air Delivery: 72 CMM</p>	8	Patna																																																						

S. N.	Description	Unit	Tonnage Class 1.5 T
1	Star Rating	No of BEE stars	3
2	Compressor	Type	Rotary
3	Rated Cooling Capacity	BTU/Hr	17573
4	Rated Cooling Capacity	Watts	5150
5	Rated Power Supply	Volts/Hz/Phase	230/50/1
6	Total power input	Watts	1490
7	EER	Rated Cooling Capacity	11.79
8	COP	Rated Cooling Capacity	3.46
9	Current Drawn	Amps	6.55
10	Fan Speed	Steps	5
11	Air Flow (Super High)	CFM	477
12	Sound level	dB	36
13	Dimensions(IDU) (WxHxD)	Mm	798x294x258
14	Dimensions(ODU) (WxHxD)	Mm	792x600x299
15	Net Weight (IDU)	Kg	11.1
16	Net Weight (ODU)	Kg	45.3

15.

Split Air Conditioner

04

Patna

Annexure – II

Schedule - II

Sl No	Name of the Item	Specification	Quantity	Place of Delivery																																																																
1	Photocopier Machine	<table border="1"> <tr><td>Copy Process</td><td>Digital Copier</td></tr> <tr><td>Type</td><td>Desktop</td></tr> <tr><td>Copy Speed</td><td>18 CPM</td></tr> <tr><td>Copier Memory (Std./Max)</td><td>32 MB / 96 MB</td></tr> <tr><td>Print Resolution</td><td>600 dpi/256 Gradations</td></tr> <tr><td>Scan Resolution</td><td>600 dpi</td></tr> <tr><td>Available Original/ Copy Paper Size</td><td>Cassette 1/2: LT- LD (17-20 lbs. Bond), Bypass Tray: ST-R - LD (17-90 lbs. Index)</td></tr> <tr><td>Paper Supply</td><td>Standard 250-Sheet Cassette, Standard 100-Sheet Bypass Tray, Optional 250-Sheet Cassette</td></tr> <tr><td>Available Copy Paper Weight</td><td>LT- LD (17-20 lbs. Bond), ST-R - LD (17-90 lbs. Index)</td></tr> <tr><td>Multiple Copying</td><td>Up to 999</td></tr> <tr><td>Reproduction Ratio</td><td>25% - 200%</td></tr> <tr><td>Warm-up Time</td><td>25 Sec.</td></tr> <tr><td>First Copy Time</td><td>7.6 Sec.</td></tr> <tr><td>Copy Density Control</td><td>Text/Text-Photo/Photo</td></tr> <tr><td>Power Supply Consumption</td><td>115 Volts/12 Amps</td></tr> <tr><td>Dimensions (WxDxH)</td><td>23.62" x 25.31" x 18.21"</td></tr> <tr><td>Weight</td><td>71.1 lbs.</td></tr> <tr><td>ADU</td><td>No</td></tr> <tr><td colspan="2">Print Specifications</td></tr> <tr><td>Standard Print</td><td>GDI Printing</td></tr> <tr><td>Print Speed</td><td>18 PPM</td></tr> <tr><td>Interface</td><td>USB 2.0</td></tr> <tr><td>Operating System</td><td>Windows 2000/XP/Vista/7/Server 2003/2008</td></tr> <tr><td>Duplex Printing</td><td>Yes (Automatic)</td></tr> <tr><td colspan="2">Scan Specifications</td></tr> <tr><td>Standard Scan</td><td>Local TWAIN Scan (Toshiba Viewer)</td></tr> <tr><td>Resolution</td><td>600 dpi</td></tr> <tr><td>Formats</td><td>BMP, TIFF, Multi-TIFF</td></tr> <tr><td>Max Scan Area</td><td>11" x 17"</td></tr> <tr><td>Interface</td><td>USB 2.0</td></tr> <tr><td>Dimensions</td><td></td></tr> <tr><td>Base:</td><td>23.6" x 25.3" x 18.2" (W x D x H)</td></tr> </table>	Copy Process	Digital Copier	Type	Desktop	Copy Speed	18 CPM	Copier Memory (Std./Max)	32 MB / 96 MB	Print Resolution	600 dpi/256 Gradations	Scan Resolution	600 dpi	Available Original/ Copy Paper Size	Cassette 1/2: LT- LD (17-20 lbs. Bond), Bypass Tray: ST-R - LD (17-90 lbs. Index)	Paper Supply	Standard 250-Sheet Cassette, Standard 100-Sheet Bypass Tray, Optional 250-Sheet Cassette	Available Copy Paper Weight	LT- LD (17-20 lbs. Bond), ST-R - LD (17-90 lbs. Index)	Multiple Copying	Up to 999	Reproduction Ratio	25% - 200%	Warm-up Time	25 Sec.	First Copy Time	7.6 Sec.	Copy Density Control	Text/Text-Photo/Photo	Power Supply Consumption	115 Volts/12 Amps	Dimensions (WxDxH)	23.62" x 25.31" x 18.21"	Weight	71.1 lbs.	ADU	No	Print Specifications		Standard Print	GDI Printing	Print Speed	18 PPM	Interface	USB 2.0	Operating System	Windows 2000/XP/Vista/7/Server 2003/2008	Duplex Printing	Yes (Automatic)	Scan Specifications		Standard Scan	Local TWAIN Scan (Toshiba Viewer)	Resolution	600 dpi	Formats	BMP, TIFF, Multi-TIFF	Max Scan Area	11" x 17"	Interface	USB 2.0	Dimensions		Base:	23.6" x 25.3" x 18.2" (W x D x H)	01	Patna
Copy Process	Digital Copier																																																																			
Type	Desktop																																																																			
Copy Speed	18 CPM																																																																			
Copier Memory (Std./Max)	32 MB / 96 MB																																																																			
Print Resolution	600 dpi/256 Gradations																																																																			
Scan Resolution	600 dpi																																																																			
Available Original/ Copy Paper Size	Cassette 1/2: LT- LD (17-20 lbs. Bond), Bypass Tray: ST-R - LD (17-90 lbs. Index)																																																																			
Paper Supply	Standard 250-Sheet Cassette, Standard 100-Sheet Bypass Tray, Optional 250-Sheet Cassette																																																																			
Available Copy Paper Weight	LT- LD (17-20 lbs. Bond), ST-R - LD (17-90 lbs. Index)																																																																			
Multiple Copying	Up to 999																																																																			
Reproduction Ratio	25% - 200%																																																																			
Warm-up Time	25 Sec.																																																																			
First Copy Time	7.6 Sec.																																																																			
Copy Density Control	Text/Text-Photo/Photo																																																																			
Power Supply Consumption	115 Volts/12 Amps																																																																			
Dimensions (WxDxH)	23.62" x 25.31" x 18.21"																																																																			
Weight	71.1 lbs.																																																																			
ADU	No																																																																			
Print Specifications																																																																				
Standard Print	GDI Printing																																																																			
Print Speed	18 PPM																																																																			
Interface	USB 2.0																																																																			
Operating System	Windows 2000/XP/Vista/7/Server 2003/2008																																																																			
Duplex Printing	Yes (Automatic)																																																																			
Scan Specifications																																																																				
Standard Scan	Local TWAIN Scan (Toshiba Viewer)																																																																			
Resolution	600 dpi																																																																			
Formats	BMP, TIFF, Multi-TIFF																																																																			
Max Scan Area	11" x 17"																																																																			
Interface	USB 2.0																																																																			
Dimensions																																																																				
Base:	23.6" x 25.3" x 18.2" (W x D x H)																																																																			
2	Projector	<p>Input Signal</p> <ul style="list-style-type: none"> • NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM <p>Display Performance</p> <ul style="list-style-type: none"> • NTSC: 560 lines • PAL: 560 line (Depends on observation of the multi-burst pattern) <p>Interfaces</p> <ul style="list-style-type: none"> • Computer/component video: D-sub 15 pin x 1 S-video: Mini DIN x 1 Composite video: RCA (Yellow) x 1 Audio in: RCA x 1 (White/Red) USB connector: Type B x 1 Monitor out: D-sub 15 pin x 1 <p>Projection Method</p> <ul style="list-style-type: none"> • Front/rear/ceiling mount <p>Pixel Number- 786,432 dots (1024 x 768) x 3</p>	01	Patna																																																																

		<p>White Light Output</p> <ul style="list-style-type: none"> Up to 2200 lumens (ISO 21118) <p>Color Light Output</p> <ul style="list-style-type: none"> Up to 2200 lumens <p>Aspect Ratio - 4:3</p> <p>Native Resolution</p> <ul style="list-style-type: none"> 1024 x 768 (XGA) <p>Resize</p> <ul style="list-style-type: none"> 640 x 480 (VGA), 1152 x 864 (SXGA), 1280 x 800 (WXGA), 1440 x 900 (WSXGA), 1400 x 1050 (SXGA+) <p>Throw Ratio Range- 1.41 – 1.70</p> <p>Projection Lens</p> <ul style="list-style-type: none"> Type Digital zoom/Manual focus F-number 1.6 – 1.74 Focal Length 18.4 mm – 22.12 mm Zoom Ratio Optical zoom 1.0 – 1.2 <p>Lamp</p> <ul style="list-style-type: none"> Lamp Type 170 W UHE Lamp Life² Up to 4000 hours (Low Light Output Mode) Up to 3000 hours (High Light Output Mode) <p>Screen Size: (Projected Distance)</p> <ul style="list-style-type: none"> 30" – 300" (2.8' – 28.5') <p>Keystone Correction</p> <ul style="list-style-type: none"> Automatic Vertical: ± 11 degrees Manual Vertical: ± 30 degrees <p>Contrast Ratio</p> <ul style="list-style-type: none"> Up to 2000:1 <p>Color Reproduction</p> <ul style="list-style-type: none"> 16.77 million colors <p>Sound Output</p> <ul style="list-style-type: none"> 1 W (Mono) <p>Operating Temperature</p> <ul style="list-style-type: none"> 41 ° to 95 °F (5 ° to 35 °C) <p>Power Supply Voltage</p> <ul style="list-style-type: none"> 100 – 240 V ±10%, 50/60 Hz <p>Power Consumption</p> <ul style="list-style-type: none"> 246 W, 3 W standby <p>Dimension</p> <ul style="list-style-type: none"> Including feet: 12.9" x 9.6" x 4.0" Excluding feet: 12.9" x 9.6" x 3.6" <p>Weight -6.2 lb/2.8 kg</p> <p>Fan Noise</p> <ul style="list-style-type: none"> 35 dB (High Brightness Mode) 28 dB (Low Brightness Mode) 		
3.	Desktop	All in one desktop with slandered UPS of 15-20 minutes back up, Intel core-i3, HDD- 500 GB or above, Screen Size-18.5" LED or above, Processor speed-4170	60	In the above mentioned 27 Districts

4.	Laptop	Processor: 5th Generation Intel® Core™ i5 processor-5200U (3MB Cache, up to 2.70 GHz); RAM: 4GB Single Channel DDR3L 1600MHz (4GBx1); HDD: 1TB 5400 rpm; OS: Windows 10 and above; Display: 15.6-inch HD (1366 x 768) Truelife LED or above; Tray load DVD Drive (Reads and Writes to DVD/CD); Tray load DVD Drive (Reads and Writes to DVD/CD); 1 HDMI™ 1.4	13	Patna			
5	Laser Colour Printer	Print Speed up to 25/26 ppm, A4/letter, 600 MHz processor with 256 MB RAM, Duty cycle up to 15000 pages per month, colour flatbed scanner with ADF, automatic duplex printing, Built in fast Ethernet.	01	Patna			
6	Laser Printer-Black & White	Print Technology: LaserJet, Print Only, Wireless Resolution (black) : Up to 600 x 600 x 2 dpi (1200 dpi effective output), Print speed letter: Up to 19 ppm (black), 150-sheet input tray, Processor speed 266 MHz, Resolution technology HP Fast Res 600, HP Fast Res 1200	04	Patna			
7	Digital Camera	Single-lens reflex digital camera, effective angle of view- Approx. 1.5 X Lens focal length, effective pixels-16.9 million, Image sensor-23.6 X 15.6 mm CMOS sensor, Total pixels- 16.9 million, Image size(pixel)- 4,928 x 3,264 [L], 3,696 x 2,448 [M], 2,464 x 1,632 [S];	01	Patna			
8	CCTV Centralized Monitoring System	8 (i) HD IP Camera (135 pcs.)		135	In the above mentioned 27 Districts		
		Feature	Parameter			Description	
		Product Code	2MP Indoor / Outdoor Dome Camera				
		Camera	Image sensor			1/3" Progressive Scan CMOS	
			Lens			2.8mm with view angle minimum 92.5° (Horizontal)	
			Minimum illumination			0.028Lux @ (F2.0, AGC ON) ,0 Lux with IR	
			Shutter Speed			1/3 s to 1/100,000 s	
			Day & Night			Mechanical ICR	
			WDR			Digital	
			IR Light			upto 30 Meter (30 x IR Leds)	
		Image	Video Compression			H.264 / MJPEG.	
			Resolution			25fps(1920x1080), 25fps (1280x960), 25fps(1280x720)60Hz: 30fps(1920x 1080), 30fps (1280 x 960), 30fps (1280 x 720)	
			Video streaming			- Simultaneous H.264, MJPEG. Two Streams - Multi-profile: resolution / compression / Frame rate / video quality. 2MP (1920X1080) @ 25 fps	
			Exposure Control			Manual/Auto	
White Balance	Auto/Fiurescent, lamp/Incandescent, lamp/Warm, light lamp/Natural light						
S/N Ratio	75 dB minimum						
DNR	3D						
Image settings	Manual (Color, Brightness, Sharpness, Contrast)						

		<table border="1"> <tr> <td rowspan="4">Network</td> <td>Security</td> <td>HTTPS, SSL, password protection, watermark, IP address filtering</td> </tr> <tr> <td>Supported Protocols</td> <td>TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6</td> </tr> <tr> <td>Dynamic Domain Name</td> <td>DynDns, NO-IP</td> </tr> <tr> <td>Users</td> <td>Access by 6 simultaneous users.</td> </tr> <tr> <td rowspan="2">Connectors</td> <td>RJ-45</td> <td>10 BASE - T / 100 BASE -TX.</td> </tr> <tr> <td>Reset</td> <td>Reset to factory default.</td> </tr> <tr> <td rowspan="4">General</td> <td>Power Consumption</td> <td><7W</td> </tr> <tr> <td>Power supply</td> <td>12 V DC ± 10% , PoE (802.3af)</td> </tr> <tr> <td>ONVIF</td> <td>Version 2.2, Profile S</td> </tr> <tr> <td>Operating Temperature</td> <td>-30 °C – 60 °C</td> </tr> <tr> <td rowspan="2"></td> <td>Approval</td> <td>UL, CE, EN, IK10 (Vandal Proof), IP66 (Weather Proof)</td> </tr> <tr> <td>Operating Humidity</td> <td>0%-95%, non-condensing</td> </tr> <tr> <td colspan="3">Warranty Support one Year</td> </tr> </table>	Network	Security	HTTPS, SSL, password protection, watermark, IP address filtering	Supported Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6	Dynamic Domain Name	DynDns, NO-IP	Users	Access by 6 simultaneous users.	Connectors	RJ-45	10 BASE - T / 100 BASE -TX.	Reset	Reset to factory default.	General	Power Consumption	<7W	Power supply	12 V DC ± 10% , PoE (802.3af)	ONVIF	Version 2.2, Profile S	Operating Temperature	-30 °C – 60 °C		Approval	UL, CE, EN, IK10 (Vandal Proof), IP66 (Weather Proof)	Operating Humidity	0%-95%, non-condensing	Warranty Support one Year																																					
Network	Security	HTTPS, SSL, password protection, watermark, IP address filtering																																																																		
	Supported Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6																																																																		
	Dynamic Domain Name	DynDns, NO-IP																																																																		
	Users	Access by 6 simultaneous users.																																																																		
Connectors	RJ-45	10 BASE - T / 100 BASE -TX.																																																																		
	Reset	Reset to factory default.																																																																		
General	Power Consumption	<7W																																																																		
	Power supply	12 V DC ± 10% , PoE (802.3af)																																																																		
	ONVIF	Version 2.2, Profile S																																																																		
	Operating Temperature	-30 °C – 60 °C																																																																		
	Approval	UL, CE, EN, IK10 (Vandal Proof), IP66 (Weather Proof)																																																																		
	Operating Humidity	0%-95%, non-condensing																																																																		
Warranty Support one Year																																																																				
8.1	CCTV Centralized Monitoring System	<table border="1"> <tr> <td colspan="3">8 (ii) Network CCTV Video Recorder (135 pcs.)</td> </tr> <tr> <td>OS</td> <td colspan="2">Embedded Linux</td> </tr> <tr> <td>CPU</td> <td colspan="2">ARM Processor</td> </tr> <tr> <td>Flash</td> <td colspan="2">256MB</td> </tr> <tr> <td>RAM</td> <td colspan="2">1GB</td> </tr> <tr> <td>Watchdog</td> <td colspan="2">Hardware + Software</td> </tr> <tr> <td>Power Restoration</td> <td colspan="2">System Restart Automatically after Power Recovery</td> </tr> <tr> <td>HDD Devices</td> <td colspan="2">Internal x2</td> </tr> <tr> <td>HDD Max. Capacity</td> <td colspan="2">6TB x2</td> </tr> <tr> <td rowspan="2">Disk Management</td> <td colspan="2">Create, Format and Remove Disk</td> </tr> <tr> <td colspan="2">HDD S.M.A.R.T</td> </tr> <tr> <td colspan="3">Video</td> </tr> <tr> <td>Video Output</td> <td colspan="2">1 x HDMI, 1 x VGA</td> </tr> <tr> <td>Resolution</td> <td colspan="2">1920 x 1080, 1280 x 720</td> </tr> <tr> <td>Graphics Decoder</td> <td colspan="2">Hardware decoding</td> </tr> <tr> <td rowspan="3">Decoding Capacity</td> <td colspan="2">H.264:</td> </tr> <tr> <td colspan="2">2560 x 1920 @ 30 fps (1-CH)</td> </tr> <tr> <td colspan="2">1920 x 1080 @ 120 fps (4-CH)</td> </tr> <tr> <td rowspan="2">Camera Position</td> <td colspan="2">1280 x 720 @ 240 fps (8-CH)</td> </tr> <tr> <td colspan="2">Change the view cell position on the Live View screens</td> </tr> <tr> <td colspan="3">External Interface</td> </tr> <tr> <td rowspan="2">USB Interface</td> <td colspan="2">Front: 2 (USB 2.0)</td> </tr> <tr> <td colspan="2">Back: 1 (USB 2.0)</td> </tr> </table>	8 (ii) Network CCTV Video Recorder (135 pcs.)			OS	Embedded Linux		CPU	ARM Processor		Flash	256MB		RAM	1GB		Watchdog	Hardware + Software		Power Restoration	System Restart Automatically after Power Recovery		HDD Devices	Internal x2		HDD Max. Capacity	6TB x2		Disk Management	Create, Format and Remove Disk		HDD S.M.A.R.T		Video			Video Output	1 x HDMI, 1 x VGA		Resolution	1920 x 1080, 1280 x 720		Graphics Decoder	Hardware decoding		Decoding Capacity	H.264:		2560 x 1920 @ 30 fps (1-CH)		1920 x 1080 @ 120 fps (4-CH)		Camera Position	1280 x 720 @ 240 fps (8-CH)		Change the view cell position on the Live View screens		External Interface			USB Interface	Front: 2 (USB 2.0)		Back: 1 (USB 2.0)		135	In the above mentioned 27 Districts
8 (ii) Network CCTV Video Recorder (135 pcs.)																																																																				
OS	Embedded Linux																																																																			
CPU	ARM Processor																																																																			
Flash	256MB																																																																			
RAM	1GB																																																																			
Watchdog	Hardware + Software																																																																			
Power Restoration	System Restart Automatically after Power Recovery																																																																			
HDD Devices	Internal x2																																																																			
HDD Max. Capacity	6TB x2																																																																			
Disk Management	Create, Format and Remove Disk																																																																			
	HDD S.M.A.R.T																																																																			
Video																																																																				
Video Output	1 x HDMI, 1 x VGA																																																																			
Resolution	1920 x 1080, 1280 x 720																																																																			
Graphics Decoder	Hardware decoding																																																																			
Decoding Capacity	H.264:																																																																			
	2560 x 1920 @ 30 fps (1-CH)																																																																			
	1920 x 1080 @ 120 fps (4-CH)																																																																			
Camera Position	1280 x 720 @ 240 fps (8-CH)																																																																			
	Change the view cell position on the Live View screens																																																																			
External Interface																																																																				
USB Interface	Front: 2 (USB 2.0)																																																																			
	Back: 1 (USB 2.0)																																																																			

Alarm In	8
Alarm Out	4
Audio	1 x 3.5 Phone Jack Audio Output 1 x 3.5 Phone Jack Audio Input (Reserved)
External HDD	1 x eSATA Port
RS232	1 Port (Reserved)
RS485	1 Port (Reserved)
Network	
Network Interface	1 x RJ-45 10/100/1000Mbps Ethernet interface
PoE	8x 802.3af Compliant PoE Ports (Total Max. 80W)
Protocols	IPv4, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, DDNS, IP Filter
Power	
Power Input	DC56V 2.5A
Power Consumption	Max. 120W
LED Indicator	
LED Indicator	Power, Status, Record, HDD1, HDD2, eSATA, Ethernet, Port1~Port8
Mechanic	
Form Factor	Desktop
Operation Buttons	Power (Front) / Reset (Back)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Humidity	0~95%
General	
Safety Certifications	CE, LVD, FCC, VCCI, C-Tick
Client PC Requirements	
Operating System	Microsoft Windows OS: XP/Vista/7/8/2008/2012
CPU	Intel Celeron or above
Memory	2 GB or above
Ethernet	10/100Mbps
Display Resolution	1024 x 768 pixels or above
Web Browser	Internet Explorer 10 (32 bit) or above
Software AP	Installation Wizard 2, ST7501, VAST
Mobile APP, Tablet APP	Connect, iViewer (iOS) Connect, iViewer (Android)
Accessories	
CD	User's Manual, Quick Installation Guide (QIG), Installation Wizard 2
Others	Power Adapter, Power Cord, Quick Installation Guide, 16 x H.D.D. Screws, 4 x H.D.D. Brackets, 1 x USB Mouse, 2 x SATA Cables

Software Information	
Record	
Maximum Channel	8
Record Throughput (MB)	64 Mbps
Network Throughput (MB)	48 Mbps
Audio Format	G.711, G.726
Video Format	MJPEG, H.264
Video Resolution	VGA, 1MP, 2MP, 3MP & 5MP Camera
Recording Time (sec.)	Pre-Record: 5 (max. 10)
	Post-Record: 20 (max. 300)
Recording Stream	Single
Recording Mode	Continuous, Schedule, Manual, Event, Activity Adaptive Streaming
Recording Setting	Recycle (unit: Day)
Recording Path	Local Path
Record Video Format	3GP
Live View (Local Display)	
Stream Application	Auto Adaptive Stream
Live View Display	8 Channel
	Multi Layout display:
	1x1, 1x3 (Corridor View), 2x2, 3x3, 1+5, 1+3, 1+1+3 (1P), 1+3+3 (1P)
	Not support de warp function from fisheye cameras
Monitor Enhancement	OSD Display (NVR), OSD Display (Camera), Camera Information, Remote I/O Control, Event Notification, Aspect Ratio
PTZ Control	Panel Control
PTZ Operation	Direction Control, Home, Iris, Preset, Patrol (Group), PiP Control
Playback (Local Display)	
Playback Display	1 Channel
	Multi Layout Display: 1x1
Playback Control	Regular (Play, Pause, Stop), Rewind, Next / Previous Frame, Speed Control, Calendar, Event, Timeline, Timeline Scale, Thumbnail (Storyboard)
Video Search	By calendar, by date/time, by alarm
Thumbnail Explorer (Storyboard)	Listing the thumbnail of recorded video (Max. 2 CH)
Monitor Enhancement	OSD Display (Camera), Event Notification, Aspect Ratio, PiP Control
Snapshot	JPEG
Video Clip Export	EXE
LiveView (Remote)	

Stream Application	Stream Selection
Audio Capability	One Way
Live View Display	8 Channel
	Multi Layout display:
	1x1, 2x2, 3x3, 1+3, 1+5
Monitor Enhancement	OSD Display (NVR), Drag & Drop, Image Freeze, Audio Control, Remote I/O Control, Event Notification, Bookmark
PTZ Control	Panel Control
PTZ Operation	Direction Control, Home, Zoom, Focus, Iris, Preset, Patrol (Group), PIP Control
Snapshot	JPEG
Playback (Remote)	
Playback Display	4 Channel
	Multi Layout display:
	1x1, 2x2, 1+3
Playback Control	Regular (Play, Pause, Stop), Next Frame, Speed Control, Calendar, Timeline, Timeline Scale, Bookmark
Monitor Enhancement	OSD Display (NVR), Drag & Drop, Audio Control, PIP Control
Snapshot	JPEG
Video Clip Export	EXE
Alarm Management	
Schedule Type	Continuous, Schedule, Manual
Event	Motion Detection, PIR Detection, Tampering Detection, Digital Input (Camera), Digital Output (Camera), Connection Abnormal, Storage Abnormal, Storage Full, Camera Network Loss, DI, DO
Action	Record, Email (Text), Email (Snapshot), FTP Buzzer, PTZ Control (Go to Preset), NVR DO, Camera DO
Recording Time (sec.)	Pre-Record: 5 (max. 10), Post-Record: 20 (max. 300)
Backup	
Manual	USB Dongle (FAT Format)
System	
User Management	User Account: 10
	User Account Time Limit: 10 mins
	User Level: Administrator / Regular User
	User Feature Definition: By Camera
Log	System, Recording, User, Error
Date & Time	Time Zone, Manual, Automatic Sync NTP, Daylight Saving Time
Firmware	Manual update
Restore Default	Supported

		<table border="1"> <tr> <td>Backup/Restore</td> <td><i>Supported</i></td> </tr> <tr> <td>Language</td> <td><i>English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Simplified Chinese, Traditional Chinese, Korean, Czech</i></td> </tr> <tr> <td colspan="2">Camera Integration</td> </tr> <tr> <td>Insert Camera</td> <td><i>Manual, Search</i></td> </tr> <tr> <td>Video (Media) Setting</td> <td><i>Compression, Resolution, FPS, Video Quality</i></td> </tr> <tr> <td>Image Setting</td> <td><i>Image Display Image Adjustment</i></td> </tr> <tr> <td>PTZ Control</td> <td><i>Panel Control</i></td> </tr> <tr> <td>PTZ Operation</td> <td><i>Direction Control, Home, Preset, Patrol (Group)</i></td> </tr> <tr> <td>Motion Detection</td> <td><i>Supported</i></td> </tr> <tr> <td colspan="2">Device Integration</td> </tr> <tr> <td>UPS</td> <td><i>APC Model Compatible</i></td> </tr> <tr> <td colspan="2">Warranty Support one Years</td> </tr> </table>	Backup/Restore	<i>Supported</i>	Language	<i>English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Simplified Chinese, Traditional Chinese, Korean, Czech</i>	Camera Integration		Insert Camera	<i>Manual, Search</i>	Video (Media) Setting	<i>Compression, Resolution, FPS, Video Quality</i>	Image Setting	<i>Image Display Image Adjustment</i>	PTZ Control	<i>Panel Control</i>	PTZ Operation	<i>Direction Control, Home, Preset, Patrol (Group)</i>	Motion Detection	<i>Supported</i>	Device Integration		UPS	<i>APC Model Compatible</i>	Warranty Support one Years																																	
Backup/Restore	<i>Supported</i>																																																									
Language	<i>English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Simplified Chinese, Traditional Chinese, Korean, Czech</i>																																																									
Camera Integration																																																										
Insert Camera	<i>Manual, Search</i>																																																									
Video (Media) Setting	<i>Compression, Resolution, FPS, Video Quality</i>																																																									
Image Setting	<i>Image Display Image Adjustment</i>																																																									
PTZ Control	<i>Panel Control</i>																																																									
PTZ Operation	<i>Direction Control, Home, Preset, Patrol (Group)</i>																																																									
Motion Detection	<i>Supported</i>																																																									
Device Integration																																																										
UPS	<i>APC Model Compatible</i>																																																									
Warranty Support one Years																																																										
8	CCTV Centralized Monitoring System	<table border="1"> <tr> <td colspan="2">8 (iii) Firewall with VPN Gateway</td> </tr> <tr> <td>GE RJ45 WAN Ports</td> <td>1</td> </tr> <tr> <td>GE RJ45 Switch Ports</td> <td>4</td> </tr> <tr> <td>USB Ports (Client / Server)</td> <td>1/1</td> </tr> <tr> <td colspan="2">System Performance</td> </tr> <tr> <td>Firewall Throughput (1518 / 512 / 64 byte UDP packets)</td> <td>800 / 800 / 800 Mbps</td> </tr> <tr> <td>New Sessions/Second (TCP)</td> <td>3,500</td> </tr> <tr> <td>Firewall Policies</td> <td>5,000</td> </tr> <tr> <td>IPsec VPN Throughput (512 byte packets)</td> <td>350 Mbps</td> </tr> <tr> <td>Gateway-to-Gateway IPsec VPN Tunnels</td> <td>20</td> </tr> <tr> <td>Client-to-Gateway IPsec VPN Tunnels</td> <td>250</td> </tr> <tr> <td>SSL-VPN Throughput</td> <td>25 Mbps</td> </tr> <tr> <td>Concurrent SSL-VPN Users (Recommended Maximum)</td> <td>80</td> </tr> <tr> <td>IPS Throughput (HTTP / Enterprise Mix)</td> <td>150/35 Mbps SSL Inspection Throughput</td> </tr> <tr> <td>Maximum Number</td> <td>20</td> </tr> <tr> <td>Maximum Number of Registered</td> <td>10</td> </tr> <tr> <td>Power Required</td> <td>100-240V AC 50-60 Hz</td> </tr> <tr> <td>Maximum Current</td> <td>110 V / 0.6 A, 220 V / 0.3 A</td> </tr> <tr> <td>Power Consumption (Average/Max.)</td> <td>10 / 12 W</td> </tr> <tr> <td>Safety</td> <td>FCC Part 15 Class B, C-Tick, VCCI, CE, UL/cUL, CB</td> </tr> <tr> <td colspan="2">Certifications</td> </tr> <tr> <td>Software Subscription</td> <td>Network Anti-Virus, IPS 1 Year</td> </tr> <tr> <td>Network Rack with wall mount</td> <td></td> </tr> <tr> <td>Network cabling with PVC pipe for camera</td> <td></td> </tr> <tr> <td>UPS 1 KVA (1)</td> <td>Power Back up system (15-20 minutes minimum)</td> </tr> <tr> <td colspan="2">Warranty Support One Year</td> </tr> <tr> <td colspan="2">Installation charge with one year maintenance charge</td> </tr> </table>	8 (iii) Firewall with VPN Gateway		GE RJ45 WAN Ports	1	GE RJ45 Switch Ports	4	USB Ports (Client / Server)	1/1	System Performance		Firewall Throughput (1518 / 512 / 64 byte UDP packets)	800 / 800 / 800 Mbps	New Sessions/Second (TCP)	3,500	Firewall Policies	5,000	IPsec VPN Throughput (512 byte packets)	350 Mbps	Gateway-to-Gateway IPsec VPN Tunnels	20	Client-to-Gateway IPsec VPN Tunnels	250	SSL-VPN Throughput	25 Mbps	Concurrent SSL-VPN Users (Recommended Maximum)	80	IPS Throughput (HTTP / Enterprise Mix)	150/35 Mbps SSL Inspection Throughput	Maximum Number	20	Maximum Number of Registered	10	Power Required	100-240V AC 50-60 Hz	Maximum Current	110 V / 0.6 A, 220 V / 0.3 A	Power Consumption (Average/Max.)	10 / 12 W	Safety	FCC Part 15 Class B, C-Tick, VCCI, CE, UL/cUL, CB	Certifications		Software Subscription	Network Anti-Virus, IPS 1 Year	Network Rack with wall mount		Network cabling with PVC pipe for camera		UPS 1 KVA (1)	Power Back up system (15-20 minutes minimum)	Warranty Support One Year		Installation charge with one year maintenance charge		01	Patna
8 (iii) Firewall with VPN Gateway																																																										
GE RJ45 WAN Ports	1																																																									
GE RJ45 Switch Ports	4																																																									
USB Ports (Client / Server)	1/1																																																									
System Performance																																																										
Firewall Throughput (1518 / 512 / 64 byte UDP packets)	800 / 800 / 800 Mbps																																																									
New Sessions/Second (TCP)	3,500																																																									
Firewall Policies	5,000																																																									
IPsec VPN Throughput (512 byte packets)	350 Mbps																																																									
Gateway-to-Gateway IPsec VPN Tunnels	20																																																									
Client-to-Gateway IPsec VPN Tunnels	250																																																									
SSL-VPN Throughput	25 Mbps																																																									
Concurrent SSL-VPN Users (Recommended Maximum)	80																																																									
IPS Throughput (HTTP / Enterprise Mix)	150/35 Mbps SSL Inspection Throughput																																																									
Maximum Number	20																																																									
Maximum Number of Registered	10																																																									
Power Required	100-240V AC 50-60 Hz																																																									
Maximum Current	110 V / 0.6 A, 220 V / 0.3 A																																																									
Power Consumption (Average/Max.)	10 / 12 W																																																									
Safety	FCC Part 15 Class B, C-Tick, VCCI, CE, UL/cUL, CB																																																									
Certifications																																																										
Software Subscription	Network Anti-Virus, IPS 1 Year																																																									
Network Rack with wall mount																																																										
Network cabling with PVC pipe for camera																																																										
UPS 1 KVA (1)	Power Back up system (15-20 minutes minimum)																																																									
Warranty Support One Year																																																										
Installation charge with one year maintenance charge																																																										

Annexure - II

Schedule-III

SL	Name of the item	Specification	Quantity	Place of delivery																
1	Director Chair	<p align="center">Front table: Size-150cm X 75cm X 74cm (approx.)</p> <p align="center">Side table: Size -105cm X 45cm X 70cm (approx.)</p> <p>Fire, Termite & Fungal Resistance, Table top shall be made of 25mm MDF board. The table shall be Mahoney finished with PU coated durable and maintenance free polish.</p> <p>One set of storage units: 3 drawer unit, Round Table under structure, foot rest for comfort during long working hours. On steel base. (Godrej , Usha Lexus, Zuari or similar brand of good quality)</p>	05	Patna																
2	Executive Chair	<table border="1"> <thead> <tr> <th>Model</th> <th>Width</th> <th>Depth</th> <th>Height</th> <th>Seat Height</th> </tr> </thead> <tbody> <tr> <td>Chair Dimension</td> <td>76.1 CM</td> <td>76.1 CM</td> <td>97.3 - 114.8 CM</td> <td>43.6-53.6 CM</td> </tr> <tr> <td>Chair Cushion</td> <td>76.1 CM</td> <td>76.1 CM</td> <td>99.2 - 116.7 CM</td> <td>43.6-53.6 CM</td> </tr> </tbody> </table>	Model	Width	Depth	Height	Seat Height	Chair Dimension	76.1 CM	76.1 CM	97.3 - 114.8 CM	43.6-53.6 CM	Chair Cushion	76.1 CM	76.1 CM	99.2 - 116.7 CM	43.6-53.6 CM	08	Patna	
Model	Width	Depth	Height	Seat Height																
Chair Dimension	76.1 CM	76.1 CM	97.3 - 114.8 CM	43.6-53.6 CM																
Chair Cushion	76.1 CM	76.1 CM	99.2 - 116.7 CM	43.6-53.6 CM																
3	S type Chair	Made up of steel frame with wire netted "S" type, Teak frame/with wire netted/double knitting with arm rest.	22	Patna																
4	Big Almirah	Slimline with locker – 900mm X 507mm X 1950mm (WXDXH)	06	Patna																
5	Executive Table	<table border="1"> <thead> <tr> <th>Model</th> <th>Width</th> <th>Depth</th> <th>Height</th> </tr> </thead> <tbody> <tr> <td>Work Desk 1</td> <td>1200</td> <td>600</td> <td>740</td> </tr> <tr> <td>Work-Desk 2</td> <td>1500</td> <td>750</td> <td>740</td> </tr> <tr> <td>Pedestal</td> <td>404</td> <td>460</td> <td>685</td> </tr> </tbody> </table>	Model	Width	Depth	Height	Work Desk 1	1200	600	740	Work-Desk 2	1500	750	740	Pedestal	404	460	685	04	Patna
Model	Width	Depth	Height																	
Work Desk 1	1200	600	740																	
Work-Desk 2	1500	750	740																	
Pedestal	404	460	685																	
6	Computer Table	Fire, Termite & Fungal Resistance, Table top shall be made of 25mm MDF board. The table shall be Mahoney finished with PU coated durable and maintenance free polish. Dimension-1200mm X 600mm X 750mm (WXDXH)	03	Patna																
7	Baby Cradle	Standard Wooden Cradle with Superior cotton fabric and mattress, Battery: No, Age group: 0 to 5 yrs., Ideal for: Boys and Girls; Feature: Swinging with lock and portable, Cradle Dimension: not less than 90(L)x37(W)x70(H) cm; (190 nos. with long chains for hanging)	490	In all 38 districts of Bihar																

ANNEXURE-III - FINANCIAL BID**Schedule - I**

Sl. No.	Name of the Items	Specification and Quantity of Goods	Price of each Unit			Total Price	
			Price of each unit Excluding taxes	Applicable Taxes per unit	Transportation, freight, local incidence support, etc.	In Figure	In words
1.	LED TV - 42"	As per Annexure-II Schedule - I					
2.	HD Dish Connection	As per Annexure-II Schedule - I					
3.	Refrigerator with Stabilizer	As per Annexure-II Schedule - I					
4.	Washing machine	As per Annexure-II Schedule - I					
5.	Geysers	As per Annexure-II Schedule - I					
6.	Air Cooler	As per Annexure-II Schedule - I					
7.	Wall mounted RO Water Purifier	As per Annexure-II Schedule - I					
8.	Exhaust Fan	As per Annexure-II Schedule - I					

9.	Search Light (Torch)	As per Annexure-II Schedule - I						
10.	Room Heater	As per Annexure-II Schedule - I						
11.	Inverter with Battery	As per Annexure-II Schedule - I						
12.	Sewing Machine	As per Annexure-II Schedule - I						
13.	Ceiling Fan	As per Annexure-II Schedule - I						
14.	Wall Fan	As per Annexure-II Schedule - I						
15.	Split Air Conditioner	As per Annexure-II Schedule - I						
TOTAL PRICE								

Note: In case of discrepancy between unit price and total price, the unit price shall prevail.

Signature of Bidder:

Name:

Business Address:

.....

Place:

ANNEXURE-III - FINANCIAL BID

Schedule - II

Sl. No.	Name of the Items	Specification and Quantity of Goods	Price of each Unit			Total Price	
			Price of each unit Excluding taxes	Applicable Taxes per unit	Transportation, freight, local incidence support, etc.	In Figure	In words
1.	Photocopier Machine	As per Annexure-II Schedule - II					
2.	Projector	As per Annexure-II Schedule - II					
3.	Desktop	As per Annexure-II Schedule - II					
4.	Laptop	As per Annexure-II Schedule - II					
5.	Laser Colour Printer	As per Annexure-II Schedule - II					
6.	Laser Printer-Black & White	As per Annexure-II Schedule - II					

7.	Digital Camera	As per Annexure-II Schedule - II					
8. [(i), (ii) and (iii)]	CCTV Centralized Monitoring System	As per Annexure-II Schedule - II					
TOTAL PRICE							

Note: *In case of discrepancy between unit price and total price, the unit price shall prevail.*

Signature of Bidder:

Name:

Business Address:

.....

Place:

ANNEXURE-III - FINANCIAL BID

Schedule - III

Sl No	Name of the Items	Specification & Quantity of Goods	Price of each Unit		Total Price	
			Price of each unit including all taxes	Transportation, freight, local incidence support, etc.	In Figure	In words
1	Director Chair	As per Annexure – II Schedule – III				
2	Executive Chair	As per Annexure – II Schedule - III				
3	'S' Type Chair	As per Annexure – II Schedule - III				
4	Big Almirah	As per Annexure – II Schedule - III				
5	Executive Table	As per Annexure – II Schedule - III				
6	Computer Table	As per Annexure – II Schedule - III				
7	Baby Cradle	As per Annexure – II Schedule - III				
TOTAL PRICE						

Note: In case of discrepancy between unit price and total price, the unit price shall prevail.

Signature of Bidder.....

Name.....

Business Address:

.....

Place:

Annexure: - IV - Experience of printing for at least three years.

Subject: Bid for the supply of _____

Detail information regarding orders executed for at least Three years .

- a) It is mandatory to appropriately fill each column. Use extra sheet if the space below is insufficient.
- b) Enclose certified copies of the purchase order in chronology.

Sl.	Reference to order no. and date for completion and delivery as per order	Amount of order	Name of the office/authority by which the order was placed	Date of completion of delivery of the order	Reason for the exemption of order or delay in supplies of order, if any
1					
2					
3					
4					
5					
6					

115

7					
8					
9					
10					

Date:

Authorized Signature of supplier with stamp

Place: